

In the Specification:

~~Page 1, line 5 insert before "the" -- and is a continuation of U.S. patent application serial no. 09/248,702 filed on February 11, 1999, --~~

In the Claims:

Kindly add new claims 17-38 as follows:

--17. A display device comprising:

a base;

first and second arms extending from the base;

first and second retainers attached respectively to the first and the second arms;

wherein at least one of the retainers is flexible such that the sports memorabilia can be inserted therebetween and supported thereby; and

~~sports memorabilia supported between the first and the second retainers.~~

--18. The display device of Claim 17, wherein the arms are flexible.--

--19. The display device of Claim 17, wherein the retainers are flexible.--

--20. The display device of Claim 17, wherein the retainers comprise flexible cups.--

--21. The display device of Claim 17 wherein the retainers comprise rigid cups.--

--22. The display device of Claim 17, wherein the retainers further comprise:

at least one component having a substantially flat surface in direct contact with the memorabilia.--

--23. The display device of Claim 22, wherein the component having the substantially flat surface is operatively connected to the retainer.--

--24. The display device of Claim 22, wherein the retainers and the component having the substantially flat surface are independent components.--

--25. The display device of Claim 24, wherein the retainer has at least one concave surface.--

--26. The display device of Claim 25, wherein the concave surface operatively connects the component having the substantially flat surface to the retainer--

--27. The display device of Claim 22, wherein the substantially flat surface in contact with the memorabilia is concave.--

--28. The display device of Claim 21, wherein the cups are made of a low friction material.--

--29. The display device of Claim 21, further comprising low friction liners positioned within the cups.--

--30. The display device of Claim 21, wherein the cups are rotatably secured to the arms.--

--31. The display device of Claim 17, wherein the retainers each comprise a rigid ring.--

--32. The display device of Claim 17, wherein the retainers each comprise a prong.--

--33. The display device of Claim 17, further comprising an arm assembly including the first and the second arms, wherein the arm assembly is rotatably secured to the base.--

--34. The display device of Claim 17, wherein ~~the arms are secured to a support rotatably mounted to the base.~~--

--35. The display device of Claim 17, wherein the base is adapted to be hung on a wall.--